

Data Sheet 10.30 Issue B



Dry Riser Landing Valve Threaded - Female Model: DRV007

Product Description

Dry riser landing valves are outlets from the riser main. The valves are situated on each floor of a high rise building and are usually housed in an outlet cabinet. Dry riser landing valves are available with PN16 inlet, Table D inlet, BSP threaded male inlet and BSP threaded female inlet. The outlets are to BS336 and come complete with cap & chain. Padlocks and straps are available on request.

Standards

Manufactured to BS5041 part 2 Flange manufactured to BS4504

Features

Manufactured from LG2 bronze


Range of inlets available, PN16, Table D, BSP male thread, BSP female thread


Compact design



Specifications

Size	65mm (2 ½")		
Material	LG2		
Pressure Rating	Tested to 22 bar		
Inlet Connection	BSP Female Threaded		
Outlet Connection	BS336 Female		
Manufactured in Accordance to	BS5041 Part 2		





Material Specifications

Item	Part Description	Qty	Material
1	Body	1	LG2
2	Disc	1	Brass
3	Stem	1	Brass
4	Valve Cap O-ring	1	Rubber
5	Valve Cap	1	Brass
6	Nut	1	Brass
7	Valve Stem O-ring	1	Rubber
8	Nut	1	Brass
9	Handwheel	1	Brass

Item	Part Description	Qty	Material
10	Handwheel Gasket	1	Steel
11	Nut M12	1	Steel
12	Tag	1	Brass
13	Spring	1	SUS304
14	Guard Knob	1	Brass
15	Nut M8	1	Steel
16	Сар	1	Plastic
17	Sealing Ring	1	Rubber
18	Cap with Chain	1	Assembly

DS: 10.30 Issue B 16/06/2017 © 2017 Rapidrop

Rapidrop Global Ltd T: +44 (0) 1733 847 510 F: +44 (0) 1733 553 958 e: rapidrop@rapidrop.com w: www.rapidrop.com